



E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 1 of 21

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

SYNONYMS

EGEN98

PROPER SHIPPING NAME

MOTOR SPIRIT or GASOLINE or PETROL

PRODUCT USE

Motor fuel for spark ignition engines. Not for aviation use. Should not be used as a solvent or cleaning agent.

SUPPLIER

Company: Neumann Petroleum Pty Ltd

Address:

23 Theodore Street

Eagle Farm

Queensland 4007

AUS

Telephone: 07 3845 6700

Emergency Tel: 1800 039 008 (24 hours)

Fax: 07 3845 6770

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

S5

RISK

Risk Codes

R12

R38

R45(2)

R46(2)

R48/20/21/22

R65

R67

Risk Phrases

■ Extremely flammable.

■ Irritating to skin.

■ May cause CANCER.

■ May cause heritable genetic damage.

■ Harmful: danger of serious damage to health by prolonged exposure through inhalation in contact with skin and if swallowed.

■ HARMFUL - May cause lung damage if swallowed.

■ Vapours may cause drowsiness and dizziness.

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 2 of 21

Section 2 - HAZARDS IDENTIFICATION

SAFETY

Safety Codes

S01

S36

S38

S401

S35

S13

S60

Safety Phrases

■ Keep locked up.

■ Wear suitable protective clothing.

■ In case of insufficient ventilation wear suitable respiratory equipment.

■ To clean the floor and all objects contaminated by this material use water and detergent.

■ This material and its container must be disposed of in a safe way.

■ Keep away from food drink and animal feeding stuffs.

■ This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
gasoline	8006-61-9	>80
ethanol	64-17-5	<10
benzene	71-43-2	<4

Section 4 - FIRST AID MEASURES

SWALLOWED

■ - If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

- If swallowed do NOT induce vomiting.

- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

- Observe the patient carefully.

- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

- Seek medical advice.

- Avoid giving milk or oils.

- Avoid giving alcohol.

EYE

■ If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.

- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

- If pain persists or recurs seek medical attention.

- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

■ If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.

- Flush skin and hair with running water (and soap if available).

- Seek medical attention in event of irritation.

INHALED

■ - If fumes or combustion products are inhaled remove from contaminated area.

- Lay patient down. Keep warm and rested.

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 3 of 21

Section 4 - FIRST AID MEASURES

-
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
 - Transport to hospital, or doctor.

NOTES TO PHYSICIAN

■ Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- - Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control the fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- WARNING: In use may form flammable/ explosive vapour-air mixtures.
- Liquid and vapour are highly flammable.

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 4 of 21

Section 5 - FIRE FIGHTING MEASURES

- Severe fire hazard when exposed to heat, flame and/or oxidisers.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: 3YE

PERSONAL PROTECTION

Glasses:

Safety Glasses.

Chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type ANO Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- - Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

- - Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 5 of 21

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- - Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Vapour may ignite on pumping or pouring due to static electricity.
- DO NOT use plastic buckets.
- Earth and secure metal containers when dispensing or pouring product.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- Keep containers securely sealed.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- - Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
- (i) : Removable head packaging;
- (ii) : Cans with friction closures and
- (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

- - Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- - Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 6 of 21

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³
Australia Exposure Standards	gasoline (Petrol (gasoline))		900
Australia Exposure Standards	ethanol (Ethyl alcohol)	1000	1880
Australia Exposure Standards	benzene (Benzene)	1	3.2

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
ethanol		3, 300 [LEL]
benzene		500

NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

MATERIAL DATA

E-GEN 98 (E10 PREMIUM UNLEADED PETROL):

Not available

GASOLINE:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

Odour threshold: 0.25 ppm.

The TLV-TWA is protective against ocular and upper respiratory tract irritation and is recommended for bulk handling of gasoline based on calculations of hydrocarbon content of gasoline vapour. A STEL is recommended to prevent mucous membrane and ocular irritation and prevention of acute depression of the central nervous system. Because of the wide variation in molecular weights of its components, the conversion of ppm to mg/m³ is approximate. Sweden recommends hexane type limits of 100 ppm and heptane and octane type limits of 300 ppm. Germany does not assign a value because of the widely differing compositions and resultant differences in toxic properties.

Odour Safety Factor (OSF)

OSF=0.042 (gasoline).

ETHANOL:

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 7 of 21

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

For ethanol:

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects. Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness. Subjects exposed to 5000 ppm to 10000 ppm experienced smarting of the eyes and nose and coughing. Symptoms disappeared within minutes. Inhalation also causes local irritating effects to the eyes and upper respiratory tract, headaches, sensation of heat intraocular tension, stupor, fatigue and a need to sleep. At 15000 ppm there was continuous lachrymation and coughing.

BENZENE:

■ Odour Threshold Value: 34 ppm (detection), 97 ppm (recognition)

NOTE: Detector tubes for benzene, measuring in excess of 0.5 ppm, are commercially available. The relative quality of epidemiological data and quantitative health risk assessments related to documented and theoretical leukaemic deaths constitute the basis of the TLV-recommendation.

One study [Dow Chemical] demonstrates a significant fourfold increase in myelogenous leukaemia for workers exposed to average benzene concentrations of about 5 ppm for an average of 9 years and that 2 out of four individuals in the study who died from leukaemia were characterised as having been exposed to average benzene levels below 2 ppm. Based on such findings the estimated risk of leukaemia in workers exposed at daily benzene concentrations of 10 ppm for 40 years is 155 times that of unexposed workers; at 1 ppm the risk falls to 1.7 times whilst at 0.1 ppm the risk is about the same in the two groups. A revision of the TLV-TWA to 0.1 ppm was proposed in 1990 but this has been revised upwards as result of industry initiatives.

Typical toxicities displayed following inhalation:

- At 25 ppm (8 hours): no effect
- 50-150 ppm: signs of intoxication within 5 hours
- 500-1500 ppm: signs of intoxication within 1 hour
- 7500 ppm: severe intoxication within 30-60 minutes
- 20000 ppm: fatal within 5-10 minutes

Some jurisdictions require that health surveillance be conducted on occupationally exposed workers. Some surveillance should emphasise (i) demography, occupational and medical history and health advice (ii) baseline blood sample for haematological profile (iii) records of personal exposure.

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 8 of 21

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION

EYE

- - Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- - Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- - Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

RESPIRATOR

- Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	ANO- AUS	-
1000	50	-	ANO- AUS
5000	50	Airline *	-
5000	100	-	ANO- 2
10000	100	-	ANO- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Yellow highly flammable liquid with strong gasoline odour; floats on water.

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 9 of 21

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Does not mix with water.

Floats on water.

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Immiscible

pH (1% solution): Not Applicable

Volatile Component (%vol): 100

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): 1.4

Autoignition Temp (°C): Not Available

State: LIQUID

Boiling Range (°C): 30- 23 0

Specific Gravity (water= 1): 0.735

pH (as supplied): Not Applicable

Vapour Pressure (kPa): 30- 100 @ 20C

Evaporation Rate: Not Available

Flash Point (°C): - 40

Upper Explosive Limit (%): 7.6

Decomposition Temp (°C): Not Available

Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

■ - Presence of incompatible materials.

- Product is considered stable.

- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions. Damage to the heart muscle can produce heart beat irregularities, ventricular fibrillation (fatal) and ECG changes. The central nervous system can be depressed. Light species can cause a sharp tingling of the tongue and cause loss of sensation there. Aspiration can cause cough, gagging, pneumonia with swelling and bleeding.

EYE

■ The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

■ Skin contact with the material may be harmful; systemic effects may result following absorption.

The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 10 of 21

Section 11 - TOXICOLOGICAL INFORMATION

Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor. Massive exposures can lead to severe central nervous system depression, deep coma and death. Convulsions can occur due to brain irritation and/or lack of oxygen. Permanent scarring may occur, with epileptic seizures and brain bleeds occurring months after exposure. Respiratory system effects include inflammation of the lungs with oedema and bleeding. Lighter species mainly cause kidney and nerve damage; the heavier paraffins and olefins are especially irritant to the respiratory system. Alkenes produce pulmonary oedema at high concentrations. Liquid paraffins may produce sensation loss and depressant actions leading to weakness, dizziness, slow and shallow respiration, unconsciousness, convulsions and death. C5-7 paraffins may also produce multiple nerve damage. Aromatic hydrocarbons accumulate in lipid rich tissues (typically the brain, spinal cord and peripheral nerves) and may produce functional impairment manifested by nonspecific symptoms such as nausea, weakness, fatigue, vertigo; severe exposures may produce inebriation or unconsciousness. Many of the petroleum hydrocarbons can sensitise the heart and may cause ventricular fibrillation, leading to death.

CHRONIC HEALTH EFFECTS

■ This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. This has been demonstrated via both short- and long-term experimentation.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

Chronic exposure to benzene may cause headache, fatigue, loss of appetite and lassitude with incipient blood effects including anaemia and blood changes. Benzene is a myelotoxicant known to suppress bone-marrow cell proliferation and to induce haematologic disorders in humans and animals. Signs of benzene-induced aplastic anaemia include suppression of leukocytes (leukopenia), red cells (anaemia), platelets (thrombocytopenia) or all three cell types (pancytopenia). Classic symptoms include weakness, purpura, and haemorrhage. The most significant toxic effect is insidious and often reversible injury to the blood forming tissue. Leukaemia may develop. Occupational exposures have shown a relationship between exposure to benzene and production of myelogenous leukaemia. There may also be a relationship between benzene exposure and the production of lymphoma and multiple myeloma. In chronic exposure, workers exhibit signs of central nervous system lesions and impairment of hearing.

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

GASOLINE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Inhalation (man) TCl₀: 900 ppm/1h

Inhalation (rat) LC₅₀: 300000 mg/m³/5m

■ Lifetime exposure of rodents to gasoline produces carcinogenicity although the relevance to humans has been questioned. Gasoline induces kidney cancer in male rats as a consequence of accumulation of the alpha₂-microglobulin protein in hyaline droplets in the male (but not female) rat kidney. Such abnormal accumulation represents lysosomal overload and leads to chronic renal tubular cell degeneration, accumulation of cell debris, mineralisation of renal medullary tubules and necrosis. A sustained regenerative proliferation occurs in epithelial cells with subsequent neoplastic transformation with continued exposure. The alpha₂-microglobulin is produced under the influence of hormonal controls in male rats but not in females and, more importantly, not in humans.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

IRRITATION

Eye (man): 500ppm/1h Moderate

Eye (man): 140ppm/8h Mild

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 11 of 21

Section 11 - TOXICOLOGICAL INFORMATION

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Oral (unspec) LD50: 500 - 5000 mg/kg [Manufacturer]

Substance has been investigated as a tumorigen.

ETHANOL:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 7060 mg/kg

Oral (human) LDLo: 1400 mg/kg

Oral (man) TDLo: 50 mg/kg

Oral (man) TDLo: 1.40 mg/kg

Oral (woman) TDLo: 256 mg/kg/12 wks

Inhalation (rat) LC50: 20, 000 ppm/10h

Inhalation (rat) LC50: 64000 ppm/4h

■ The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

IRRITATION

Skin (rabbit):20 mg/24hr- Moderate

Skin (rabbit):400 mg (open)- Mild

Eye (rabbit):100mg/24hr- Moderate

Eye (rabbit): 500 mg SEVERE

BENZENE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (man) LDLo: 50 mg/kg

Oral (rat) LD50: 930 mg/kg

Inhalation (rat) LC50: 10000 ppm/7h

Inhalation (human) LCLo: 2000 ppm/5m

Inhalation (man) TCLo: 150 ppm/1y - I

Inhalation (human) TCLo: 100 ppm

■ The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

IRRITATION

SKIN (rabbit):20 mg/24h - Moderate

Eye (rabbit): 2 mg/24h - SEVERE

CARCINOGEN

gasoline	International Agency for Research on Cancer (IARC) Carcinogens	Group	2B
ethanol	International Agency for Research on Cancer (IARC) Carcinogens	Group	1
benzene	International Agency for Research on Cancer (IARC) Carcinogens	Group	1
benzene	Australia National Model Regulations for the Control of Scheduled Carcinogenic Substances	Schedule	2
benzene	Australia Exposure Standards - Carcinogens	Carcinogen Category	see Haz. Substances information

REPROTOXIN

benzene	ILO Chemicals in the electronics industry that have toxic effects on reproduction	Reduced fertility or sterility	H si
---------	---	--------------------------------	------

Section 12 - ECOLOGICAL INFORMATION

■ DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

GASOLINE:

■ For petroleum derivatives:

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 12 of 21

Section 12 - ECOLOGICAL INFORMATION

Chemical analysis for all individual compounds in a petroleum bulk product released to the environment is generally unrealistic due to the complexity of these mixtures and the laboratory expense. Determining the chemical composition of a petroleum release is further complicated by hydrodynamic, abiotic, and biotic processes that act on the release to change the chemical character.

The longer the release is exposed to the environment, the greater the change in chemical character and the harder it is to obtain accurate analytical results reflecting the identity of the release. After extensive weathering, detailed knowledge of the original bulk product is often less valuable than current site-specific information on a more focused set of hydrocarbon components. Health assessment efforts are frequently frustrated by three primary problems: (1) the inability to identify and quantify the individual compounds released to the environment as a consequence of a petroleum spill; (2) the lack of information characterizing the fate of the individual compounds in petroleum mixtures; and (3) the lack of specific health guidance values for the majority of chemicals present in petroleum products. To define the public health implications associated with exposure to petroleum hydrocarbons, it is necessary to have a basic understanding of petroleum properties, compositions, and the physical, chemical, biological, and toxicological properties of the compounds most often identified as the key chemicals of concern.

Environmental fate:

Petroleum products released to the environment migrate through soil via two general pathways: (1) as bulk oil flow infiltrating the soil under the forces of gravity and capillary action, and (2) as individual compounds separating from the bulk petroleum mixture and dissolving in air or water. When bulk oil flow occurs, it results in little or no separation of the individual compounds from the product mixture and the infiltration rate is usually fast relative to the dissolution rate. Many compounds that are insoluble and immobile in water are soluble in bulk oil and will migrate along with the bulk oil flow. Factors affecting the rate of bulk oil infiltration include soil moisture content, vegetation, terrain, climate, rate of release (e.g., catastrophic versus slow leakage), soil particle size (e.g., sand versus clay), and oil viscosity (e.g., gasoline versus motor oil).

As bulk oil migrates through the soil column, a small amount of the product mass is retained by soil particles. The bulk product retained by the soil particles is known as "residual saturation".

Depending upon the persistence of the bulk oil, residual saturation can potentially reside in the soil for years. Residual saturation is important as it determines the degree of soil contamination and can act as a continuing source of contamination for individual compounds to separate from the bulk product and migrate independently in air or groundwater. Residual saturation is important as it determines the degree of soil contamination and can act as a continuing source of contamination for individual compounds to separate from the bulk product and migrate independently in air or groundwater. When the amount of product released to the environment is small relative to the volume of available soil, all of the product is converted to residual saturation and downward migration of the bulk product usually ceases prior to affecting groundwater resources. Adverse impacts to groundwater may still occur if rain water infiltrates through soil containing residual saturation and initiates the downward migration of individual compounds. When the amount of product released is large relative to the volume of available soil, the downward migration of bulk product ceases as water-saturated pore spaces are encountered. If the density of the bulk product is less than that of water, the product tends to "float" along the interface between the water saturated and unsaturated zones and spread horizontally in a pancake-like layer, usually in the direction of groundwater flow. Almost all motor and heating oils are less dense than water. If the density of the bulk product is greater than that of water, the product will continue to migrate downward through the water table aquifer under the continued influence of gravity. Downward migration ceases when the product is converted to residual saturation or when an impermeable surface is encountered.

As the bulk product migrates through the soil column, individual compounds may separate from the mixture and migrate independently. Chemical transport properties such as volatility, solubility, and sorption potential are often used to evaluate and predict which compounds will likely separate from the mixture. Since petroleum products are complex mixtures of hundreds of compounds, the compounds characterized by relatively high vapor pressures tend to volatilise and enter the vapor phase. The exact composition of these vapors depends on the composition of the original product. Using gasoline as an example, compounds such as butane, propane, benzene, toluene, ethylbenzene and xylene are preferentially volatilised. Because volatility represents transfer of the compound from the product or liquid phase to the air phase, it is expected that the concentration of that compound in the product or liquid phase will decrease as the concentration in the air phase increases. In general, compounds having a vapor pressure in excess of 10-2 mm Hg are more likely to be present in the air phase than in the liquid phase. Compounds characterized by vapor pressures less than 10-7 mm Hg are more likely to be associated with the liquid phase. Compounds possessing vapor pressures that are less than 10-2 mm Hg, but greater than 10-7 mm Hg, will have a tendency to exist in both the air and the liquid phases. Lighter petroleum products such as gasoline contain constituents with higher water solubility and volatility

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 13 of 21

Section 12 - ECOLOGICAL INFORMATION

and lower sorption potential than heavier petroleum products such as fuel oil.

Data compiled from gasoline spills and laboratory studies indicate that these light-fraction hydrocarbons tend to migrate readily through soil, potentially threatening or affecting groundwater supplies. In contrast, petroleum products with heavier molecular weight constituents, such as fuel oil, are generally more persistent in soils, due to their relatively low water solubility and volatility and high sorption capacity. Solubility generally decreases with increasing molecular weight of the hydrocarbon compounds. For compounds having similar molecular weights, the aromatic hydrocarbons are more water soluble and mobile in water than the aliphatic hydrocarbons and branched aliphatics are less water-soluble than straight-chained aliphatics. Aromatic compounds in petroleum fuels may comprise as much as 50% by weight; aromatic compounds in the C6-C13, range made up approximately 95% of the compounds dissolved in water.

Indigenous microbes found in many natural settings (e.g., soils, groundwater, ponds) have been shown to be capable of degrading organic compounds. Unlike other fate processes that disperse contaminants in the environment, biodegradation can eliminate the contaminants without transferring them across media. The final products of microbial degradation are carbon dioxide, water, and microbial biomass. The rate of hydrocarbon degradation depends on the chemical composition of the product released to the environment as well as site-specific environmental factors. Generally the straight chain hydrocarbons and the aromatics are degraded more readily than the highly branched aliphatic compounds. The n-alkanes, n-alkyl aromatics, and the aromatics in the C10-C22 range are the most readily biodegradable; n-alkanes, n-alkyl aromatics, and aromatics in the C5-C9 range are biodegradable at low concentrations by some microorganisms, but are generally preferentially removed by volatilisation and thus are unavailable in most environments; n-alkanes in the C1-C4 ranges are biodegradable only by a narrow range of specialized hydrocarbon degraders; and n-alkanes, n-alkyl aromatics, and aromatics above C22 are generally not available to degrading microorganisms. Hydrocarbons with condensed ring structures, such as PAHs with four or more rings, have been shown to be relatively resistant to biodegradation. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. A large proportion of the water-soluble fraction of the petroleum product may be degraded as the compounds go into solution. As a result, the remaining product may become enriched in the alicyclics, the highly branched aliphatics, and PAHs with many fused rings.

In almost all cases, the presence of oxygen is essential for effective biodegradation of oil. Anaerobic decomposition of petroleum hydrocarbons leads to extremely low rates of degradation. The ideal pH range to promote biodegradation is close to neutral (6-8). For most species, the optimal pH is slightly alkaline, that is, greater than 7. The moisture content of the contaminated soil will affect biodegradation of oils due to dissolution of the residual compounds, dispersive actions, and the need for microbial metabolism to sustain high activity. The moisture content in soil affects microbial locomotion, solute diffusion, substrate supply, and the removal of metabolic by-products. Biodegradation rates in soils are also affected by the volume of product released to the environment. At concentrations of 0.5% of oil by volume, the degradation rate in soil is fairly independent of oil concentrations. However, as oil concentration rises, the first order degradation rate decreases and the oil degradation half-life increases. Ultimately, when the oil reaches saturation conditions in the soil (i.e., 30-50% oil), biodegradation virtually ceases.

Excessive moisture will limit the gaseous supply of oxygen for enhanced decomposition of petroleum hydrocarbons. Most studies indicate that optimum moisture content is within 50-70% of the water holding capacity.

All biological transformations are affected by temperature. Generally, as the temperature increases, biological activity tends to increase up to a temperature where enzyme denaturation occurs. The presence of oil should increase soil temperature, particularly at the surface. The darker color increases the heat capacity by adsorbing more radiation. The optimal temperature for biodegradation to occur ranges from 18 C to 30 C. Minimum rates would be expected at 5 C or lower.

ETHANOL:

■ Fish LC50 (96hr.) (mg/l):	13480
■ Algae IC50 (72hr.) (mg/l):	1450
■ log Kow (Sangster 1997):	- 0.3
■ BOD5:	63%
■ ThOD:	2.1
■ Half- life Soil - High (hours):	24
■ Half- life Soil - Low (hours):	2.6
■ Half- life Air - High (hours):	122
■ Half- life Air - Low (hours):	12.2
■ Half- life Surface water - High (hours):	26

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 14 of 21

Section 12 - ECOLOGICAL INFORMATION

■ Half- life Surface water - Low (hours):	6.5
■ Half- life Ground water - High (hours):	52
■ Half- life Ground water - Low (hours):	13
■ Aqueous biodegradation - Aerobic - High (hours):	26
■ Aqueous biodegradation - Aerobic - Low (hours):	6.5
■ Aqueous biodegradation - Anaerobic - High (hours):	104
■ Aqueous biodegradation - Anaerobic - Low (hours):	26
■ Aqueous biodegradation - Removal secondary treatment - High (hours):	67%
■ Photooxidation half- life water - High (hours):	3.20E+05
■ Photooxidation half- life water - Low (hours):	8020
■ Photooxidation half- life air - High (hours):	122
■ Photooxidation half- life air - Low (hours):	12.2

■ When ethanol is released into the soil it readily and quickly biodegrades but may leach into ground water; most is lost by evaporation. When released into water the material readily evaporates and is biodegradable. Ethanol does not bioaccumulate to an appreciable extent.

The material is readily degraded by reaction with photochemically produced hydroxy radicals; release into air will result in photodegradation and wet deposition.

Environmental Fate:

TERRESTRIAL FATE: An estimated Koc value of 1 indicates that ethanol is expected to have very high mobility in soil. Volatilisation of ethanol from moist soil surfaces is expected to be an important fate process given a Henry's Law constant of 5×10^{-6} atm-m³/mole. The potential for volatilization of ethanol from dry soil surfaces may exist based upon an extrapolated vapor pressure of 59.3 mm Hg. Biodegradation is expected to be an important fate process for ethanol based on half-lives on the order of a few days for ethanol in sandy soil/groundwater microcosms

AQUATIC FATE: An estimated Koc value of 1 indicates that ethanol is not expected to adsorb to suspended solids and sediment. Volatilisation from water surfaces is expected based upon a Henry's Law constant of 5×10^{-6} atm-m³/mole. Using this Henry's Law constant and an estimation method, volatilisation half-lives for a model river and model lake are 3 and 39 days, respectively. An estimated BCF= 3, from a log Kow of -0.31 suggests bioconcentration in aquatic organisms is low. Hydrolysis and photolysis in sunlit surface waters is not expected to be an important environmental fate process for ethanol since this compound lacks functional groups that hydrolyse or absorb light under environmentally relevant conditions. Ethanol was degraded with half-lives on the order of a few days in aquatic studies conducted using microcosms constructed with a low organic sandy soil and groundwater, indicating it is unlikely to be persistent in aquatic environments(8).

ATMOSPHERIC FATE: Ethanol, which has an extrapolated vapor pressure of 59.3 mm Hg at 25 deg C, is expected to exist solely as a vapor in the ambient atmosphere. Vapor-phase ethanol is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 5 days, calculated from its rate constant of 3.3×10^{-12} m³/molecule-sec at 25 deg C.

Ecotoxicity:

log Kow : -0.31- -0.32

Half-life (hr) air : 144

Half-life (hr) H₂O surface water : 144

Henry's atm m³ /mol: 6.29E-06

BOD 5 if unstated: 0.93-1.67,63%

COD : 1.99-2.11,97%

ThOD : 2.1.

BENZENE:

■ Hazardous Air Pollutant:	Yes
■ Fish LC50 (96hr.) (mg/l):	32
■ BCF<100:	24
■ log Kow (Prager 1995):	2.31
■ log Kow (Sangster 1997):	2.13
■ log Pow (Verschueren 1983):	2.13
■ Half- life Soil - High (hours):	384
■ Half- life Soil - Low (hours):	120
■ Half- life Air - High (hours):	501
■ Half- life Air - Low (hours):	50.1
■ Half- life Surface water - High (hours):	384

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 15 of 21

Section 12 - ECOLOGICAL INFORMATION

■ Half- life Surface water - Low (hours):	120
■ Half- life Ground water - High (hours):	17280
■ Half- life Ground water - Low (hours):	240
■ Aqueous biodegradation - Aerobic - High (hours):	384
■ Aqueous biodegradation - Aerobic - Low (hours):	120
■ Aqueous biodegradation - Anaerobic - High (hours):	17280
■ Aqueous biodegradation - Anaerobic - Low (hours):	2688
■ Aqueous biodegradation - Removal secondary treatment - High (hours):	100%
■ Aqueous biodegradation - Removal secondary treatment - Low (hours):	44%
■ Aqueous photolysis half- life - High (hours):	16152
■ Aqueous photolysis half- life - Low (hours):	2808
■ Photolysis maximum light absorption - High (nano- m):	268
■ Photolysis maximum light absorption - Low (nano- m):	239
■ Aqueous photolysis half- life - High (hours):	16152
■ Aqueous photolysis half- life - Low (hours):	2808
■ Photooxidation half- life water - High (hours):	3.20E+05
■ Photooxidation half- life water - Low (hours):	8021
■ Photooxidation half- life air - High (hours):	501
■ Photooxidation half- life air - Low (hours):	50.1

■ For hydrocarbons:

Environmental fate:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some hydrocarbon will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions hydrocarbons degrade to water and carbon dioxide, while under anaerobic processes they produce water, methane and carbon dioxide.

Alkenes have low log octanol/water partition coefficients (Kow) of about 1 and estimated bioconcentration factors (BCF) of about 10; aromatics have intermediate values (log Kow values of 2-3 and BCF values of 20-200), while C5 and greater alkanes have fairly high values (log Kow values of about 3-4.5 and BCF values of 100-1,500

The estimated volatilisation half-lives for alkanes and benzene, toluene, ethylbenzene, xylene (BTEX) components were predicted as 7 days in ponds, 1.5 days in rivers, and 6 days in lakes. The volatilisation rate of naphthalene and its substituted derivatives were estimated to be slower

Indigenous microbes found in many natural settings (e.g., soils, groundwater, ponds) have been shown to be capable of degrading organic compounds. Unlike other fate processes that disperse contaminants in the environment, biodegradation can eliminate the contaminants without transferring them across media.

The final products of microbial degradation are carbon dioxide, water, and microbial biomass. The rate of hydrocarbon degradation depends on the chemical composition of the product released to the environment as well as site-specific environmental factors. Generally the straight chain hydrocarbons and the aromatics are degraded more readily than the highly branched aliphatic compounds. The n-alkanes, n-alkyl aromatics, and the aromatics in the C10-C22 range are the most readily biodegradable; n-alkanes, n-alkyl aromatics, and aromatics in the C5-C9 range are biodegradable at low concentrations by some microorganisms, but are generally preferentially removed by volatilisation and thus are unavailable in most environments; n-alkanes in the C1-C4 ranges are biodegradable only by a narrow range of specialised hydrocarbon degraders; and n-alkanes, n-alkyl aromatics, and aromatics above C22 are generally not available to degrading microorganisms. Hydrocarbons with condensed ring structures, such as PAHs with four or more rings, have been shown to be relatively resistant to biodegradation. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. In almost all cases, the presence of oxygen is essential for effective biodegradation of oil. The ideal pH range to promote biodegradation is close to neutral (6-8). For most species, the optimal pH is slightly alkaline, that is, greater than 7.

All biological transformations are affected by temperature. Generally, as the temperature increases, biological activity tends to increase up to a temperature where enzyme denaturation occurs.

Atmospheric fate: Alkanes, isoalkanes, and cycloalkanes have half-lives on the order of 1-10 days, whereas

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 16 of 21

Section 12 - ECOLOGICAL INFORMATION

alkenes, cycloalkenes, and substituted benzenes have half-lives of 1 day or less. Photochemical oxidation products include aldehydes, hydroxy compounds, nitro compounds, and peroxyacyl nitrates. Alkenes, certain substituted aromatics, and naphthalene are potentially susceptible to direct photolysis.

Ecotoxicity:

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

The values of log Kow for individual hydrocarbons increase with increasing carbon number within homologous series of generic types. Quantitative structure activity relationships (QSAR), relating log Kow values of single hydrocarbons to toxicity, show that water solubility decreases more rapidly with increasing Kow than does the concentration causing effects. This relationship varies somewhat with species of hydrocarbon, but it follows that there is a log Kow limit for hydrocarbons, above which, they will not exhibit acute toxicity; this limit is at a log Kow value of about 4 to 5. It has been confirmed experimentally that for fish and invertebrates, paraffinic hydrocarbons with a carbon number of 10 or higher (log Kow >5) show no acute toxicity and that alkylbenzenes with a carbon number of 14 or greater (log Kow >5) similarly show no acute toxicity. QSAR equations for chronic toxicity also suggest that there should be a point where hydrocarbons with high log Kow values become so insoluble in water that they will not cause chronic toxicity, that is, that there is also a solubility cut-off for chronic toxicity. Thus, paraffinic hydrocarbons with carbon numbers of greater than 14 (log Kow >7.3) should show no measurable chronic toxicity.

■ For benzene:

log Kow: 1.95-2.15

log Koc: 1.7-2

Koc: 85

log Kom: 1.04-2.56

Half-life (hr) air: 2.4-501

Half-life (hr) H₂O surface water: 4.81-384

Half-life (hr) H₂O ground: 240-17280

Half-life (hr) soil: 48-922

Henry's Pa m³ /mol: 441-595

Henry's atm m³ /mol: 5.43E-03

BOD 5 if unstated: 2.18

COD: 0.25-2.8

ThOD: 3.1

BCF: 3.5-3.9

Log BCF: 0.54-1.48

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.); benzene: 10 ug/l (WHO guideline)

Soil Guidelines: Dutch Criteria: 0.05 mg/kg (detection limit) target; 1 mg/kg (intervention)

Air Quality Standards: 1 ppb averaging time 1 year (UK)

No safe level recommended due to carcinogenic properties (WHO Guideline)

If benzene is released to the atmosphere it remains predominantly in the vapour phase.

Vapour phase benzene is not subject to direct photolysis but reacts with photochemically produced hydroxyl radicals (half-life approximately 13.4 days). Reaction time in polluted atmospheres which contain nitrogen oxide (NO) or sulfur dioxide (SO₂) is accelerated (half-life 4-6 hours); products of photooxidation include phenol, nitrophenols, nitrobenzene, formic acid and peroxyacetyl nitrates.

In water, benzene is rapidly volatilised (half-life 2.7 hours).

In soil benzene undergoes rapid volatilisation; it is not absorbed, to any appreciable degree, by sediments.

Benzene does not bioaccumulate in the food chain.

Environmental Fate

Terrestrial fate: A Koc value of 85, indicates that benzene is expected to have high mobility in soil.

Volatilisation of benzene from moist soil surfaces is expected to be an important fate process given a Henry's Law constant of 5.43x10⁻³ atm-cu m/mole. The potential for volatilisation of benzene from dry soil surfaces may exist based upon a vapor pressure of 94.8 mm Hg. Benzene is expected to biodegrade in soils based on a biodegradation study in a base-rich para-brownish soil where 20 ppm benzene was 24% degraded in 1 week, 44% in 5 weeks, and 47% in 10 weeks. Anaerobic degradation of benzene in soil is not expected to be an important loss process based on various studies. In one study of chemical biotransformation under nitrate- and sulfate-reducing conditions, benzene was found to be stable for 60 days. In a related study, benzene did not undergo biodegradation in situ nor in laboratory controlled soil samples under denitrifying conditions.

Aquatic fate: The Koc value of 85, indicates that benzene is not expected to adsorb to sediment and suspended solids in water. Volatilisation from water surfaces is expected based upon the Henry's Law constant. Using

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 17 of 21

Section 12 - ECOLOGICAL INFORMATION

this Henry's Law constant, volatilisation half-lives for a model river and model lake are estimated to be 1 hr and 3.5 days, respectively. Anaerobic degradation of benzene in water is not expected to be an important loss process based on various studies. In one study of chemical biotransformation under nitrate- and sulfate-reducing conditions, benzene was found to be stable for 60 days. In aqueous solution, benzene will react with hydroxyl radical at a reaction rate of 7.8×10^9 L/mol sec; using the average OH radical concentration (1.0×10^{-17} molec/cu cm), benzene would have a half-life of 103 days. A BCF ranging from 1.1-20 suggests the potential for bioconcentration in aquatic organisms is low.

Aquatic fate: Evaporation was the primary loss mechanism in winter in a mesocosm experiment which simulated a northern bay where the half-life was 13 days. In spring and summer the half-lives were 23 and 3.1 days, respectively. In these cases biodegradation plays a major role and takes about 2 days. However, acclimation is critical and this takes much longer in the colder water in spring. According to one experiment, benzene has a half-life of 17 days due to photodegradation which could contribute to benzene's removal. In situations of cold water, poor nutrients, or other conditions less conducive to microbial growth, photolysis will play a important role in degradation. The half-life of benzene in sea water is about 5 hrs based on its high Henry's Law constant of 5.56×10^{-3} atm-cu m/mole.

Atmospheric fate: According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere benzene, which has a vapour pressure of 94.8 mm Hg at 25 deg C, is expected to exist solely as a vapor in the ambient atmosphere. Vapour-phase benzene is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 13 days, calculated from its rate constant of 1.23×10^{-12} cu cm/molecule-sec at 25 deg C. The half-life in polluted atmospheres which contain nitrogen oxides or sulfur dioxide has been observed to shorten to 4-6 hrs. Vapour-phase benzene is also degraded in the atmosphere by atmospheric ozone radicals at an extremely slow rate; the half-life for this reaction in air is estimated to be 170,000 days. The reaction rate of benzene with nitrate radical in the atmosphere is estimated to be less than 0.3×10^{-16} cu cm/molecule sec at 25 deg C; the half-life for this reaction in air is estimated to be greater than or equal to 111 days based on an average concentration of nitrate radicals of 2.4×10^8 molec/cu cm. Benzene has a maximum absorbance frequency of 253 nm suggesting that direct photolysis will not be an important degradation process. Due to benzene's high water solubility, it may be removed from the atmosphere by rainfall

Ecotoxicity:

Fish LC50 (96 h): bass (*Morone saxatilis*) 5.8-11 mg/l

Fish LC50 24-96 h) fathead minnow (*Pimephales promelus*) 33-35 mg/l (softwater); 24-32 mg/l (hardwater); bluegill sunfish (*Lepomis macrochirus*) 22 mg/l; goldfish (*Carassius auratus*) 36 mg/l (softwater); mosquito fish (*Gambusia affinis*) 395 mg/l

Fish LC50 (24-48 h): bluegill sunfish (*Lepomis macrochirus*) 20 mg/l

Fish LC50 (24 h): goldfish (*Carassius auratus*) 46 mg/l; blue gill sunfish (*Lepomis macrochirus*) 34 mg/l

Fish LC100 (2 h): blue gill sunfish (*Lepomis macrochirus*) 60 mg/l

Fish LC50 (14 d): guppy (*Poecilia reticulata*) 63 mg/l

Fish LC50 (1 h): brown trout yearlings (*Salmo trutta*) 12 mg/l (static assay)

Ciliate LC100 (24 h): *Tetrahymena pyriformis* 12.8 mmole/l

Grass shrimp (*Palaemonetes pugio*) LC50 (96 h): 27 ppm

Shrimp (*Crangon francorum*) LC50 (96 h): 20 mg/l

Crab larvae (*Cancer magister*) LC50 (96 h): 108 ppm

Mexican axolotl (*Ambystoma mexicanum*) LC50 (48 h): 370 mg/l (3-4 weeks after hatching)

Clawed toad LC50 (48 h): 190 mg/l (3-4 weeks after hatching).

■ Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

■ The material is classified as an ecotoxin* because the Fish LC50 (96 hours) is less than or equal to 0.1 mg/l

* Classification of Substances as Ecotoxic (Dangerous to the Environment)

Appendix 8, Table 1

Compiler's Guide for the Preparation of International Chemical Safety Cards: 1993 Commission of the European Communities.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
E- Gen 98 (E10 Premium Unleaded Petrol)		No data		
gasoline		No data		

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 18 of 21

Section 12 - ECOLOGICAL INFORMATION

ethanol	LOW	MED	LOW	HIGH
benzene	LOW	HIGH	MED	MED

Section 13 - DISPOSAL CONSIDERATIONS

- - Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID

HAZCHEM: 3YE (ADG7)

ADG7:

Class or division:	3	Subsidiary risk:	None
UN No.:	1203	UN packing group:	II
Special provisions:	243	Packing Instructions:	None
Notes:	None	Limited quantities:	1 L
Portable tanks and bulk containers - Instructions:	T4	Portable tanks and bulk containers - Special provisions:	TP1
Packagings and IBCs - Packing instruction:	P001, IBC02	Packagings and IBCs - Special packing provisions:	None

Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL

Land Transport UNDG:

Class or division:	3	Subsidiary risk:	None
UN No.:	1203	UN packing group:	II

Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL

Air Transport IATA:

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1203	Packing Group:	II
EMS Number:	F- E, S- E	Special provisions:	243 944
Limited Quantities:	1 L		

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 19 of 21

Section 14 - TRANSPORTATION INFORMATION

Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

REGULATIONS

E-Gen 98 (E10 Premium Unleaded Petrol) (CAS: None):
No regulations applicable

Regulations for ingredients

gasoline (CAS: 8006-61-9) is found on the following regulatory lists;

- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards
- International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List
- OECD Representative List of High Production Volume (HPV) Chemicals

gasoline (CAS: 86290-81-5) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia Hazardous Substances
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards
- International Agency for Research on Cancer (IARC) Carcinogens
- International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List
- OECD Representative List of High Production Volume (HPV) Chemicals

ethanol (CAS: 64-17-5) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Illicit Drug Reagents/Essential Chemicals - Category III
- Australia Inventory of Chemical Substances (AICS)
- Australia National Pollutant Inventory
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- IMO IBC Code Chapter 18: List of products to which the Code does not apply
- IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
- IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO
- International Agency for Research on Cancer (IARC) Carcinogens
- International Air Transport Association (IATA) Dangerous Goods Regulations
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals

benzene (CAS: 71-43-2) is found on the following regulatory lists;

- Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)
- Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)
- Australia - Australian Capital Territory Environment Protection Regulation Ecosystem maintenance - Organic chemicals - Non-pesticide anthropogenic organics
- Australia - Australian Capital Territory Environment Protection Regulation Pollutants entering waterways - Domestic water quality
- Australia - New South Wales Hazardous Substances Prohibited for Specific Uses
- Australia - New South Wales Hazardous Substances Requiring Health Surveillance
- Australia - New South Wales Notifiable Carcinogens
- Australia - Tasmania Hazardous Substances Requiring Health Surveillance
- Australia - Western Australia Carcinogenic substances to be used only for purposes approved by the Commissioner
- Australia - Western Australia Hazardous Substances Requiring Health Surveillance
- Australia Exposure Standards
- Australia Exposure Standards Currently Under Review
- Australia Hazardous Substances
- Australia Hazardous Substances Requiring Health Surveillance
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia National Model Regulations for the Control of Scheduled Carcinogenic Substances
- Australia National Pollutant Inventory
- Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 - Hazardous Substances Requiring Health Surveillance
- Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 - Scheduled Carcinogenic Substance
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix J (Part 2)

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 20 of 21

Section 15 - REGULATORY INFORMATION

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 7
Great Lakes Binational Toxics Strategy Substances (U.S. and Canada) - Level II Substances
IMO IBC Code Chapter 17: Summary of minimum requirements
IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO
IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards
International Agency for Research on Cancer (IARC) Carcinogens
International Chemical Secretariat (ChemSec) REACH SIN* List (*Substitute It Now!) 1.0
OECD Representative List of High Production Volume (HPV) Chemicals
OSPAR List of Chemicals for Priority Action

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
gasoline	8006- 61- 9, 86290- 81- 5

REPRODUCTIVE HEALTH GUIDELINES

■ Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
ethanol	1880 mg/m3	NA	NA	NA	Yes
benzene	0.05 mg/m3	1000	D	1.4	-

■ These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 7-Aug-2009

Print Date: 7-Aug-2009

continued...

E-GEN 98 (E10 PREMIUM UNLEADED PETROL)

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2009

NC317ECP

CHEMWATCH 4694-66

Version No:2.0

CD 2009/2 Page 21 of 21

Section 16 - OTHER INFORMATION

This is the end of the MSDS.